




Double Glazing Systems

Magnetglaze *a magnetic fixing system*



Magnetglaze



Magnetglaze Pro



**PLEASE READ INSTRUCTIONS THOROUGHLY
BEFORE CUTTING OR FITTING THIS SYSTEM**

TUBEWAY (SALES) LIMITED

Elton Park, Hadleigh Road, Ipswich, IP2 0HN

Tel: 01473 251051 Fax: 01473 236044

email: sales@tubeway.co.uk website: www.tubeway.co.uk


EASYFIX is a Registered Trademark of Tubeway (Sales) Limited

The Magnetglaze System

MAGNETGLAZE is the latest addition to the double glazing systems that we offer from the EASYFIX range. It comprises two strips, one metal and the other magnetic. The metal strip is white faced and has self-adhesive tape on one side. This strip is placed on the window frame around the area to be glazed. The magnetic strip, which is also self-adhesive is placed around the edges of the plastic sheet.

MAGNETGLAZE is available in a convenient 5m pre-pack.

MAGNETGLAZE is intended for internal use only and NOT recommended for use with glass. Always fit to the main frame and not to opening windows.




HELPFUL HINTS - For larger windows (1200mm x 1200mm or bigger) we strongly recommend placing a couple of screws under the glazing panel to support the sheet. This will prevent the sheet from slipping down and becoming detached.

TOOLS REQUIRED - Tape measure, pencil and strong pair of scissors.



Measuring up for your Plastic Sheeting



1. Measure the existing window pane, vertically (measurement A) and horizontally (measurement B). **This is the visible glass only and does not include any frame.**
2. Add 25mm to each measurement A & B. This will give you the size of the sheet required. Also ensure you have a minimum 19mm mounting surface on each side of your window.

Measuring up for your MAGNETGLAZE

3. You will require 2 lengths at measurement 'A' plus 25mm and 2 lengths at measurement 'B' for your window (**do not** add 25mm to measurement B). Add these together to find out how many 5m pre-pack kits you will need.

USING MAGNETGLAZE STEP BY STEP

4. Remove strips from packaging and begin by cutting and sticking the black magnetic strip to each edge of the plastic sheet.
5. Now hold the panel to the window frame so that it overlaps equally on each edge.
6. Draw a pencil line around the sheet on the frame
7. Cut and fit the white metal strip to the window frame, sticking it just inside the pencil marks.
8. Offer up the glazing panel to the window and click into place.

It is always best to remove double glazing in summer to allow ventilation.

The Magnetglaze Pro System




MAGNETGLAZE PRO combines the simplicity of magnetic fixing with the aesthetic appeal of framing your plastic sheet. It comprises two parts, a rigid pvc frame profile which has the magnetic strip attached and a self-adhesive metal strip.

MAGNETGLAZE PRO is available in a 2.44m lengths and white or brown in colour


MAGNETGLAZE is intended for internal use only and NOT recommended for use with glass. Always fit to the main frame and not to opening windows.

HELPFUL HINTS - For larger windows (1200mm x 1200mm or bigger) we strongly recommend placing a couple of screws under the glazing panel to support the sheet. This will prevent the sheet from slipping down and becoming detached.

TOOLS REQUIRED - Fine tooth saw, tape measure, mitre block and pencil.



Measuring up for your Plastic Sheeting



1. Measure the existing window pane, vertically (measurement A) and horizontally (measurement B). **This is the visible glass only and does not include any frame.**
2. Add 30mm to each measurement A & B. This will give you the size of the sheet required. Also ensure you have a minimum 20mm mounting surface on each side of your window.

Measuring up for your MAGNETGLAZE PRO

3. You will require 2 lengths at measurement 'A' plus 33mm and 2 lengths at measurement 'B' plus 33mm for your window. Add these together to find out how many 2.44m lengths you will need.

USING MAGNETGLAZE PRO STEP BY STEP

4. Remove the white metal strip from the length of Magnetglaze PRO.
5. Working with your plastic panel, measure the side to which you want to place a strip of Magnetglaze PRO. Add 3mm to this and squarely cut a length of Magnetglaze PRO to suit. Repeat for each side of the panel.
6. Using the outer corner as a reference (see diagram), insert the mitre bead and cut a 45° mitre using the fine toothed saw and mitre block. Repeat this step for all lengths.
7. Now fit the Magnetglaze PRO to the edges of the panel.
8. Hold the panel to the window frame so that it overlaps equally on each edge.
9. Draw a pencil line around the sheet on the frame.
10. Cut and fit the white metal strip to the window frame, sticking it just inside the pencil marks.
11. Offer up the glazing panel to the window and click into place.

